





REV	ECN NO.	APPD
A	HC-19-0084	ZO

规格 Specifications

额定负荷 Rating	DC 12V/50mA
接触电阻 Contact Resistance	500mΩ max.
绝缘电阻 Insulation resistance	DC100V 60S 100MΩ min.
抗电强度 Dielectric strength	AC250V(50~60HZ) 60S min.
操作力 Operation force	≤180±30gf ≥240±50gf
寿命试验 Operating Life	300,000 cycles
行程 Travels	0.13±0.05mm



RECOMMENDED P.C.B. LAYOUT
安装尺寸图

LAND PATTERN PLAN
印刷电路板焊盘参考图

PRODUCT NO.: 1TS015B*****

轻触开关

3X2系列

外形:

A=两脚

B=两脚无按柄

按点颜色:
底座颜色:
贴膜颜色:

操作力度:

初始颜色
则不启用

120=120gf
160=160gf
180=180gf
200=200gf
220=220gf
240=240gf
330=330gf

材料:

0=双弹片

3=三弹片

依次增加

产品高度(H):

0.45=0.45mm

其它:

CT=编带(非编带,不启用)

手感:

0=常规(弹片)

1=大手感(弹片)

2=小手感(弹片)

3=特殊手感(弹片)

4	FILM	1	POLYAMIDE	WHITE
3	DOVE	2	SUS301	Ag-PLATED
2	HOUSING	1	POLYAMIDE	BLACK
1	TERMINAL	1	PHOSPHOR BRONZE	Ag-PLATED
ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
X. ± 0.2	X. ± 0.2	NAME(INTENDED USE)	HON YUAN	
.X ± 0.1	.X' ± 0.1	3X2 SERIES	HON YUAN PRECISION IND. CO.,LTD.	
.XX ± 0.01	.XX' ± 0.01	TACT SWITCHES	SHENZHEN, CHINA.	
.XXX ± 0.002	.XXX' ± 0.005	PART NO.(INTENDED USE)	TITLE:	
		1TS015B*****	PRODUCT DRAWING	
		APPD: ZO 5/23/2019	DWG NO.: 1TS015B	
		CHKD M.H.Li 5/23/2019	SCALE SHEET	
		DR: Y.Y.Chen 5/23/2019	25/1 1/1	
			REV. A	