




REV	ECN NO.	APPD
A	HC-19-0220	ZO

规格 Specifications

额定负荷 Rating	DC 12V/50mA
接触电阻 Contact Resistance	500mΩ max.
绝缘电阻 Insulation resistance	DC:100V 60S 100MΩ min.
抗电强度 Dielectric strength	AC250V(50-60HZ) 60S min.
操作力 Operation force	≥200±40gf
寿命试验 Operating Life	100,000 cycles
行程 Travels	0.13±0.05mm



PRODUCT NO.: 1TS028B***-045**

- 轻触开关
2. 8X1.9 系列
- 外形:
- A=四脚
 - B=四脚无按柄
- 按点颜色:
- 底座颜色:
- 贴膜颜色:
- 操作力度:
- 100=100gf
 - 160=160gf
 - 225=225gf
- 初始颜色
则不启用
- 手感:
- 0=常规(弹片)
 - 1=大手感(弹片)
 - 2=小手感(弹片)
 - 3=特殊手感(弹片)
- 材质:
- 0=初始材质
 - 1=新增材质
 - 3=3个弹片依次增加
- 其它:
- CT=编带(非编带,不启用)

4	FILM	1	POLYAMIDE	WHITE
3	DOME	3	SUS301	Ag-PLATED
2	HOUSING	1	POLYAMIDE	BLACK
1	TERMINAL	1	PHOSPHOR BRONZE	Ag-PLATED
ITEM		PART NAME	QUANTITY	MATERIAL
				FINISH
X. ± 0.2	X.* ± 0.2*	UNITS	MM	
.X ± 0.1	.X* ± 0.1*	MAT'L		
.XX ± 0.01	.XX* ± 0.01*	PART NO.(INTENDED USE)		
.XXX ± 0.002	.XXX* ± 0.005*	FINISH		
Q'TY		TITLE:		
APPD: ZO 12/06/2019		PRODUCT DRAWING		
CHKD: M.H.LI 12/06/2019		DWG NO.: 1TS028B		
DR-Y.Y.Chen 12/06/2019		SCALE SHEET REV.		
		25/1 2/2 A		

THESE DIMENSIONS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.

HON YUAN
HON YUAN PRECISION IND. CO.,LTD.
SHENZHEN, CHINA.