

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

NOTES1:

UL Standard

- 1.Rated Voltage/Current : 300V / 10A
- 2.Withstanding Voltage : AC1600V/1Min.
- 3.Wire Range : 26~12AWG

IEC Standard

1.

Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0KV
Rate Voltage(V)	320V
Rate Current(A)	20A

2.Wire Range : 0.2~2.5mm²

NOTES2:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 5.00/5.08mm, Poles : N=02~22P/02~16P
- 3.Stripping length : 9-10mm
- 4.Operating temperature: -40°C~+105°C
- 5.Undimensioned Tolerances:


Pitch range in mm		Nominal dimension range in mm			
TO	Over	TO	Over	TO	Over
6	10	10	30	30	60
10	24	30	60	60	100
		60	100	100	150
				150	
					0.1/10
					<
					±2'

6.RoHS Compliance

2EDGKDFM - 5.0/5.08 - XXP - 1Y - 00A (H)

(Series No.) (Pitch) (Poles) (Single Pitch) (Color): 1.(Grey)
 2.(Blue)
 3.(Black)
 4.(Green)
 5.(Orange)
 6.(Red)
 7.(Transparent)
 8.(Yellow)
 9.(White)

(RoHS)
 00A-(Standard)

DETACHED LISTS	PART NO.:	 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD			
	APPD:	NAME:			
	CHKD:	2EDGKDFM-5.0/5.08-XXP-1Y-00A(H)			
	DRFT:	TITLE: CUSTOMER DRAWING		REV	DO
		DRAWING NO.:		SHEET	1/1
THIRD ANGLE PROJECTION				SCALE	1:1

