







REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
1			INITIAL RELEASE	2023.03.14	Yy_D



- NOTES:
- PRODUCT MEETS CONTROLLED SUBSTANCES SPEC. ROHS 2.0
1. MATERIAL:
- 1.1 HOUSING: SPS, UL94V-0; COLOR: BLACK.
- 1.2 CONTACT: BRASS.
2. FINISH:
- 2.1 CONTACT: 100u"MIN. TIN PLATING ON SOLDER TAIL AREA.
- 50u". NICKEL UNDERPLATING OVERALL.
3. ELECTRICAL SPECIFICATION:
- 3.1 VOLTAGE RATING: 50V MAX. AC/DC.
- 3.2 CURRENT RATING: 3A MAX. AC/DC.
- 3.3 WITHSTANDING VOLTAGE: 1000V AC/MINUTE.
- 3.4 TEMPERATURE RANGE: -40°C~+125°C
- 3.5 INSULATION RESISTANCE: 1000MΩ.
- 3.6 CONTACT RESISTANCE: ≤5MΩ MAX.AFTER ENVIRONMENT TESTING:≤10MΩ



Poles	Dimensions (mm)		
	A	B	C
2*06	19.10	16.50	11.00
2*08	23.50	20.90	15.40
2*10	27.90	25.30	19.80
2*12	32.30	29.70	24.20
2*14	36.70	34.10	28.60
2*16	41.10	38.50	33.00
2*18	45.50	43.00	37.40
2*20	49.90	47.40	41.80

DIM	TOL	DIM	TOL
x.	±0.35	x.	±2'
.x	±0.30		
.xx	±0.25		

570CBG-033R*** **

CUSTOMER CODE

T: TRAY

G: TUBE

PIN:

12: 12PIN

.....

40: 40PIN

COLOR:

1: BLACK 2: NATURAL

3: GRAY

LOGO:

1: WITH LOGO



2: WITHOUT LOGO

R:RoHS


H:HALOGEN-FREE

WAFER


		DEREN SHENZHEN DEREN ELECTRONIC CO., LTD			
DRAW NO.		CUSTOMER DRAWING	DATE	TITLE: WAFER 2.20PH 13H R/A DIP CONN	
***		DESIGN: Yy_D	2023.03.14	P/N:SEE TABLE	
REV. 1		CHECK:		SHEET: 1/3	
		APPROVAL:		SCALE: 1:1	UNIT: mm




2*06PIN




2*20PIN




2*08PIN




2*18PIN




2*10PIN



2*16PIN




2*12PIN



2*14PIN


DIM	TOL	DIM	TOL
X.	±0.35	X.	±2°
.X	±0.30		
.XX	±0.25		

	DEREN	SHENZHEN DEREN ELECTRONIC CO., LTD	
	CUSTOMER DRAWING		DATE
	DESIGN:	Yy_D	2023.03.14
	CHECK:		
REV.	1	APPROVAL:	
DRAW NO.		P/N:SEE TABLE	
***		SHEET:	2/3
		SCALE:	1:1
		UNIT:	mm



图示一
1.将产品依次装入管中

图示二
2.装满产品的管子包扎



图示三
3.将每扎管子包扎

胶带ADHESIVE
TAPE

标签LABEL

图示四
4.装箱，封胶

说明:

- 1.将产品依图示方向放入真空管内，方向须一致，每个真空管放的产品数量依Pin数不同而不同，具体详见包装明细表，真空管两头用胶塞塞住，如图示一。
- 2.将装好产品的真空管平放在桌面上以3PCS为一排然后叠放3列或2列为1把如图二或图三，整理好后用PE膜将1把真空管两头PE膜缠绕包好，并在左边PE膜处贴1PCS产品标签，如图示二。
- 3.将上步完成的产品以每把进行包扎，包装成一整扎，以图示三
- 4.将包扎好产品放入纸箱内，并将纸箱用胶带封好，在其侧面右上角贴上出货标签。
- 5.纸箱规格：600*200*180mm 真空管规格：600*29.4*22.3mm
- 6.纸箱厚度：6~7mm

PIN数	每支真空产品 数量PCS/管	每箱真空管数量 PCS管/箱	每箱包装数量 PCS/箱
2*06	30	48	1440
2*08	24	48	1152
2*10	20	48	960
2*12	17	48	816
2*14	15	48	720
2*16	13	48	624
2*18	12	48	576
2*20	11	48	528

DIM	TOL	DIM	TOL
x.		x.	
.x			
.xx			

		DEREN					
		SHENZHEN DEREN ELECTRONIC CO., LTD					
		CUSTOMER DRAWING		DATE		TITLE: WAFER 2.20PH 13H R/A DIP CONN	
		DRAW NO. ***		DESIGN: Yy_D	2023.03.14		P/N:SEE TABLE
		CHECK:				SHEET: 3/3 	
REV.	1	APPROVAL:				SCALE: N/A	UNIT: mm