




REV.	DESCRIPTION	DESIGN	APPROVAL	DATE
A0	NEW VERSION	Yuan	Jerry	2024.03.15

Specifications:
Contact resistance: $\leq 10\text{m}\Omega$;
Insulation resistance: $\geq 1000\text{M}\Omega$;
Rated voltage: 250V AC/DC;
Rated current: 5.0A AC/DC;
Withstand Voltage: 1000V AC/minute;
Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$;
Housing: LCP UL94V-0.BLACK;
Contacts: Brass/MATTE Sn-plated;
Solder Tabs: Brass/MATTE Sn-plated;

Part no:
991-XX X - X 1 1 0
Colour: 1: White; 2: Black
Plating: 1: Sn; 3: Au
No. of Poles: 02~24

PART No.	Poles	Dimensions(mm)	
		A	B
991-021-2110	2x1	/	6.65
991-041-2110	2x2	3.00	9.65
991-061-2110	2x3	6.00	12.65
991-081-2110	2x4	9.00	15.65
991-101-2110	2x5	12.00	18.65
991-121-2110	2x6	15.00	21.65
991-141-2110	2x7	18.00	24.65
991-161-2110	2x8	21.00	27.65
991-181-2110	2x9	24.00	30.65
991-201-2110	2x10	27.00	33.65
991-221-2110	2x11	30.00	36.65
991-241-2110	2x12	33.00	39.65

X.± 0.50	X.*± 0.5*	 Guangdong JiDe Precision Electronics Co., Ltd 广东济德精密电子有限公司	TITLE: 3.0Pitch Wafer 90°SMT			PART NO. 991-XXX-X110				
.X± 0.30	.X.*± 0.3*									
.XX± 0.20	.XX.*± /		APPD:			DWG NO: C-991-XXX-X110				
.XXX± 0.10	.XXX.*± /									
UNITS:	mm	The information in this document is property of JIDCON company and should not be copied or reproduced in any other way, without written permission.	CHKD:				SCALE	SHEET	REV.	
			DRAW:				1:1	1/2	A0	

