

	1	2	3	4	5	6	7	8																																																																																																																																																																						
						版 本	变 更 内 容	工程确认	日 期																																																																																																																																																																					
A																																																																																																																																																																														
B																																																																																																																																																																														
C	技术指标 (Technical Index): - 塑件表面应光滑、无毛边、无明显收缩、缺陷、裂纹等现象。 (The surface of the plastic parts should be smooth, no rough edges, no obvious shrinkage, defects, cracks and other phenomena.) - 温度范围(Temperature range): -25° C~+85° C. - 额定电压(Rated voltage): 50V, AC/DC(-等效). - 接触电阻(Contact resistance): ≤0.03 Ω. - 绝缘电阻(Insulation resistance): ≥500M Ω. - 产品料号(Product material No.): BTC05202-*** ** NO OF CKT (产品PIN数) Plating (电镀方式) 0:端子全雾锡(Terminal all mist tin) T:TUBE管装 1:端子全金(Terminal G/F OVERALL) R:TAPE & REEL卷装 Packing (包装方式) 适用扁平线(Applicable Flat Cable)					5.20																																																																																																																																																																								
D																																																																																																																																																																														
E	<table><tr><th>序号 No.</th><th>品名Name</th><th>材质Material</th></tr><tr><td>①</td><td>0.5拉拔3代胶芯(H2.0) 0.5 Pitch ZIF Type 3 Housing (H=2.0)</td><td>LCP UL94V-0 本色 Natural</td></tr><tr><td>②</td><td>0.5拉拔下接端子(H2.0) 0.5 Pitch H2.0 ZIF R/A Type Under terminal</td><td>铜合金/表面镀锡 Copper Alloy/ Tin Plating</td></tr><tr><td>③</td><td>0.5拉拔3代后盖(H2.0) 0.5 Pitch ZIF Type 3 Actuator (H=2.0)</td><td>LCP UL94V-0 黑色 Black</td></tr><tr><td>④</td><td>0.5拉拔3代焊片(H2.0) 0.5 Pitch ZIF Type 3 Fitting Nail (H=2.0)</td><td>铜合金/表面镀锡 Copper Alloy/ Tin Plating</td></tr></table>					序号 No.	品名Name	材质Material	①	0.5拉拔3代胶芯(H2.0) 0.5 Pitch ZIF Type 3 Housing (H=2.0)	LCP UL94V-0 本色 Natural	②	0.5拉拔下接端子(H2.0) 0.5 Pitch H2.0 ZIF R/A Type Under terminal	铜合金/表面镀锡 Copper Alloy/ Tin Plating	③	0.5拉拔3代后盖(H2.0) 0.5 Pitch ZIF Type 3 Actuator (H=2.0)	LCP UL94V-0 黑色 Black	④	0.5拉拔3代焊片(H2.0) 0.5 Pitch ZIF Type 3 Fitting Nail (H=2.0)	铜合金/表面镀锡 Copper Alloy/ Tin Plating	<table><tr><th>CTK</th><th>DIMA</th><th>DIMB</th><th>DIMC</th><th>DIMD</th></tr><tr><td>4</td><td>1.50</td><td>2.56</td><td>7.60</td><td></td></tr><tr><td>5</td><td>2.00</td><td>3.06</td><td>8.10</td><td></td></tr><tr><td>6</td><td>2.50</td><td>3.56</td><td>8.60</td><td></td></tr><tr><td>7</td><td>3.00</td><td>4.06</td><td>9.10</td><td></td></tr><tr><td>8</td><td>3.50</td><td>4.56</td><td>9.60</td><td></td></tr><tr><td>9</td><td>4.00</td><td>5.06</td><td>10.10</td><td></td></tr><tr><td>10</td><td>4.50</td><td>5.56</td><td>10.60</td><td></td></tr><tr><td>11</td><td>5.00</td><td>6.06</td><td>11.10</td><td></td></tr><tr><td>12</td><td>5.50</td><td>6.56</td><td>11.60</td><td></td></tr><tr><td>13</td><td>6.00</td><td>7.06</td><td>12.10</td><td></td></tr><tr><td>14</td><td>6.50</td><td>7.56</td><td>12.60</td><td></td></tr><tr><td>15</td><td>7.00</td><td>8.06</td><td>13.10</td><td></td></tr><tr><td>16</td><td>7.50</td><td>8.56</td><td>13.60</td><td></td></tr><tr><td>17</td><td>8.00</td><td>9.06</td><td>14.10</td><td></td></tr><tr><td>18</td><td>8.50</td><td>9.56</td><td>14.60</td><td></td></tr><tr><td>19</td><td>9.00</td><td>10.06</td><td>15.10</td><td></td></tr><tr><td>20</td><td>9.50</td><td>10.56</td><td>15.60</td><td></td></tr><tr><td>21</td><td>10.0</td><td>11.06</td><td>16.01</td><td></td></tr><tr><td>22</td><td>10.50</td><td>11.56</td><td>16.60</td><td></td></tr><tr><td>23</td><td>11.00</td><td>12.06</td><td>17.10</td><td></td></tr><tr><td>24</td><td>11.50</td><td>12.56</td><td>17.60</td><td></td></tr><tr><td>25</td><td>12.00</td><td>13.06</td><td>18.10</td><td></td></tr><tr><td>26</td><td>12.50</td><td>13.56</td><td>18.60</td><td></td></tr><tr><td>27</td><td>13.00</td><td>14.06</td><td>19.10</td><td></td></tr><tr><td>28</td><td>13.50</td><td>14.56</td><td>19.60</td><td></td></tr><tr><td>29</td><td>14.00</td><td>15.06</td><td>20.10</td><td></td></tr><tr><td>30</td><td>14.50</td><td>15.56</td><td>20.60</td><td></td></tr><tr><td>31</td><td>15.00</td><td>16.06</td><td>21.10</td><td></td></tr><tr><td>32</td><td>15.50</td><td>16.56</td><td>21.60</td><td></td></tr></table>				CTK	DIMA	DIMB	DIMC	DIMD	4	1.50	2.56	7.60		5	2.00	3.06	8.10		6	2.50	3.56	8.60		7	3.00	4.06	9.10		8	3.50	4.56	9.60		9	4.00	5.06	10.10		10	4.50	5.56	10.60		11	5.00	6.06	11.10		12	5.50	6.56	11.60		13	6.00	7.06	12.10		14	6.50	7.56	12.60		15	7.00	8.06	13.10		16	7.50	8.56	13.60		17	8.00	9.06	14.10		18	8.50	9.56	14.60		19	9.00	10.06	15.10		20	9.50	10.56	15.60		21	10.0	11.06	16.01		22	10.50	11.56	16.60		23	11.00	12.06	17.10		24	11.50	12.56	17.60		25	12.00	13.06	18.10		26	12.50	13.56	18.60		27	13.00	14.06	19.10		28	13.50	14.56	19.60		29	14.00	15.06	20.10		30	14.50	15.56	20.60		31	15.00	16.06	21.10		32	15.50	16.56	21.60	
序号 No.	品名Name	材质Material																																																																																																																																																																												
①	0.5拉拔3代胶芯(H2.0) 0.5 Pitch ZIF Type 3 Housing (H=2.0)	LCP UL94V-0 本色 Natural																																																																																																																																																																												
②	0.5拉拔下接端子(H2.0) 0.5 Pitch H2.0 ZIF R/A Type Under terminal	铜合金/表面镀锡 Copper Alloy/ Tin Plating																																																																																																																																																																												
③	0.5拉拔3代后盖(H2.0) 0.5 Pitch ZIF Type 3 Actuator (H=2.0)	LCP UL94V-0 黑色 Black																																																																																																																																																																												
④	0.5拉拔3代焊片(H2.0) 0.5 Pitch ZIF Type 3 Fitting Nail (H=2.0)	铜合金/表面镀锡 Copper Alloy/ Tin Plating																																																																																																																																																																												
CTK	DIMA	DIMB	DIMC	DIMD																																																																																																																																																																										
4	1.50	2.56	7.60																																																																																																																																																																											
5	2.00	3.06	8.10																																																																																																																																																																											
6	2.50	3.56	8.60																																																																																																																																																																											
7	3.00	4.06	9.10																																																																																																																																																																											
8	3.50	4.56	9.60																																																																																																																																																																											
9	4.00	5.06	10.10																																																																																																																																																																											
10	4.50	5.56	10.60																																																																																																																																																																											
11	5.00	6.06	11.10																																																																																																																																																																											
12	5.50	6.56	11.60																																																																																																																																																																											
13	6.00	7.06	12.10																																																																																																																																																																											
14	6.50	7.56	12.60																																																																																																																																																																											
15	7.00	8.06	13.10																																																																																																																																																																											
16	7.50	8.56	13.60																																																																																																																																																																											
17	8.00	9.06	14.10																																																																																																																																																																											
18	8.50	9.56	14.60																																																																																																																																																																											
19	9.00	10.06	15.10																																																																																																																																																																											
20	9.50	10.56	15.60																																																																																																																																																																											
21	10.0	11.06	16.01																																																																																																																																																																											
22	10.50	11.56	16.60																																																																																																																																																																											
23	11.00	12.06	17.10																																																																																																																																																																											
24	11.50	12.56	17.60																																																																																																																																																																											
25	12.00	13.06	18.10																																																																																																																																																																											
26	12.50	13.56	18.60																																																																																																																																																																											
27	13.00	14.06	19.10																																																																																																																																																																											
28	13.50	14.56	19.60																																																																																																																																																																											
29	14.00	15.06	20.10																																																																																																																																																																											
30	14.50	15.56	20.60																																																																																																																																																																											
31	15.00	16.06	21.10																																																																																																																																																																											
32	15.50	16.56	21.60																																																																																																																																																																											
F						<table><tr><th>页码(SHEET)</th><th>1/1</th><th>单位(UNIT): MM</th></tr><tr><th>版本(REV)</th><th>A1</th><th>比例(SCALE)</th></tr><tr><th>日期(DATE)</th><td>2021. 10. 12</td><td rowspan="3"></td></tr><tr><th>设计(DESIGN)</th><td>LUO</td></tr><tr><th>审核(CHECKED)</th><td>ROGER LI</td></tr><tr><th>图号(DWG NO)</th><td>BTC05202-***-**LW</td><th>核准(APPROVED)</th><td>ROC ZHAO</td></tr></table> These drawings and specifications are Dongguan Bozhong Technology Co Ltd.The property should not be copied. Without Dongguan Bozhong Technology Co. Ltd.Prior written consent to copy or use in any way. Email at info@bozhongelectric.com				页码(SHEET)	1/1	单位(UNIT): MM	版本(REV)	A1	比例(SCALE)	日期(DATE)	2021. 10. 12		设计(DESIGN)	LUO	审核(CHECKED)	ROGER LI	图号(DWG NO)	BTC05202-***-**LW	核准(APPROVED)	ROC ZHAO																																																																																																																																																				
页码(SHEET)	1/1	单位(UNIT): MM																																																																																																																																																																												
版本(REV)	A1	比例(SCALE)																																																																																																																																																																												
日期(DATE)	2021. 10. 12																																																																																																																																																																													
设计(DESIGN)	LUO																																																																																																																																																																													
审核(CHECKED)	ROGER LI																																																																																																																																																																													
图号(DWG NO)	BTC05202-***-**LW	核准(APPROVED)	ROC ZHAO																																																																																																																																																																											