

RoHS

REV	ECN NO.	DESCRIPTION	DESIGN	APPROVAL	DATE
A1	NEW	更换图框			2024.05.24

SPECIFICATIONS

- Current rating: 3A
- Temperature range: -40°C ~ +105°C
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 600V AC/ minute.
- Contact resistance: 20mΩ Max.

Material:

Insulator Material:PBT (UL 94V-0) Black

Contact Material:Copper Alloy

Plating:Matte Tin or gold plated over Nickel

Ordering Code:

EH254R-12-xxP
1 2

1.序列号

2.Pin位数: 2x03=06P

注明:

1: A 在18P及18P以上Pin位才有。

2: B 仅60P与64P有

No.of PIN/ROW	Dimension	
	A	B
2x03	5.08	26.82
2x04	7.62	29.36
2x05	10.16	31.90
2x07	15.24	36.98
2x08	17.78	39.52
2x10	22.86	44.60
2x12	27.94	49.68
2x13	30.48	52.22
2x15	35.56	57.30
2x17	40.64	62.38
2x20	48.26	70.00
2x25	60.96	82.70
2x30	73.66	95.40
2x32	78.74	100.48

X.±0.50	X.°±
.X±0.25	.X°±
.XX±0.15	.XX°±
.XXX±0.10	.XXX°±
UNITS:	mm

THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF XFCN AND SHALL
NOT BE REPRODUCED, COPIED OR CUED IN
ANY MANNER WITHOUT THE PRIOR
WRITTEN CONSENT OF XFCN

PART NO: EH254R-12-xxP		XFCN 兴飞连接器		
TITLE: 2.54mm Ejector Header Connectors		0769-82001899		
		www.xfconn.com		
		DWG NO:		
APPD	Chen ZhiQiang			
CHKD	Liu Wei	VIEW		
DRAW	Chen HongJiang	SCALE	SHEET	REV
DATE	2024.07.19	NONE	1/1	A1

P.C.B Layout