



name部位名称	unit 符号	specification 尺寸规格
No. of cinducors导体数	pin	(N)P
margin width边距	M	1.0±0.08
Pintch间距	P	1.0±0.08
Total pitch总间距	SP	(N-1)×0.1±0.08
width总宽度	W	(N-1)×1.0±0.08
strip length 1端子长度1	S1	4±0.5
strip length 2端子长度2	S2	4±0.5
reinforeing tape length 1 补强板长度1	B1	8±2.0
reinforeing tape length 2 补强板长度2	B2	8±2.0
Total length产品长度	TL	(L)±2MM
Insulation length绝缘体长度	IL	(L-S1-S2)±2
Thickness insulation产品厚度	T	0.121±0.03
Cable thickness末端厚度	T1/T2	0.303±0.03
slanting切割斜度	A	< 0.3



型号：FC-1.0B-XXP-XXXMM

1.0: 1.0mm Pitch 间距

B: oppositedirectionge表示同向

NP: PIN位数

XXX: 总长度

MM: 单位

						APPROVALS		DATE		DEALON德之隆® ELECTRONICS CO.,LTD			
						DRAWN	G.M.Chen	2015/5/22					
						CHECKED				TITLE: FPC软排线			
						APPROVALS				PART NO. FC-1.0B-XXP-XXXMM			
	A		NEW			TOLERANCES ARE		30~以上	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	SHEET 1 OF 1
					10~30			±0.20					
					5~10			±0.15					
					~ 5			±0.10					
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.			DRAWING NO.		PROJ:		