

Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PBT+30%G.F UL94V-0, 颜色: 黑色.

Housing: PBT+30%G.F UL94V-0, Color: Black

端子: 黄铜, 镍底30u"MIN, 表面镀普金

Contact: Brass, GOLD PLATING OVER ALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 1 AMP

Rated Current: 1 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.



Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V/分钟.

Withstanding Voltage: AC 500V/Minute.

温度范围: -40° C to +105° C

Temperature Range: -40° C to +105° C



Ordering Information

IDC2 - XX 3 54 XX A T X 1

NO. OF PINS
6-64P

Contact Plating
Full of Gold

A0=0.8u"

A1=1u"

A2=1.5u"

A3=2u"

A4=3u"

A5=5u"

A6=10u"

A7=15u"

A8=20u"

A9=30u"

S1=Q di nary Ti n Pl ated

S2=Matte Ti n Pl ated

S3=Ti n-pl ated H gh-t emper at ure

Contact Plating
Semi-gold

B0=0.8u"

B1=1u"

B2=1.5u"

B3=2u"

B4=3u"

B5=5u"

B6=10u"

B7=15u"

B8=20u"

B9=30u"

INSULATOR
MATERIAL:

A: PBT

BACK
MATERIAL:

G: Grey 427

E: Grey 413

W: White

U: Blue

				OPERATION		SCALE		Fit		Yxcon 东莞市宇熙精密连接器有限公司			
				X.X	±0.25	UNIT		MM		www.yxcon.com Dongguan Yuxi Electronic Co., Ltd.			
				X.XX	±0.20	SIZE	A4	DESIGN	周芳杰 2022.04.08	PART NO.	IDC2-XX354XXATX1		
				X.XXX	±0.10	SHEET	1/1	CHECK		TITLE:	2.00 IDC 塑高5.4 弹片式 三件式 带凸点		
REV	DATE	SYMBOL	MODIFICATION DESCRIPTION	ANGLE	±3°	PROJ.		APPROVE		Customer No.			
				DIM	TOL								