





Circuit Diagram

PCB Layout(Pattern side)



NO.1			
PART NO	H	PART NO	H
A	4.3	O	11
B	4.5	P	11.5
C	5	Q	12
D	5.5	R	12.5
E	6	S	13
F	6.5	T	13.5
G	7	U	14
H	7.5	V	15
I	8	W	16
J	8.5	X	17
K	9	Y	18
L	9.5	Z	19
M	10	1	15.5
N	10.5		

NO.2	
PART NO	vigor
1	90±30
2	130±30
3	180±30
4	250±30
5	350±50

NO.3	
PART NO	MATERIAL/QTY
S	SUS/1PC
C	C5210/1PC
D	SUS/2PCS
F	C5210/2PCS

NO.4-NO.5	
PART NO	NOTE
01~99	SERIAL NUMBER

⑤	Terminal	—	4	Brass(0.30t)	Plating silver	—
④	Contact	—	1	F.Ag/SUS	—	—
③	Base	—	1	Nylon	Black	—
②	Cover	—	1	SPCC	Plating Nickel	—
①	Keystoke	—	1	Nylon	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS			DATE		HRO韩泰® ELECTRONICS CO.,LTD			
DRAWN		J.X.Zhang	2013/5/30					
CHECKED					TITLE: TACT SWITCHS			
APPROVALS					PART NO. K2-1102DP-□□□W-□□			
TOLERANCES ARE		30~以上	±0.30	ANGLE ±2°	UNIT: mm		SCALE: 1:1	PROJ: 
		10~30	±0.20		SCALE: 1:1		PROJ: 	
		5~10	±0.15		SCALE: 1:1		PROJ: 	
		~ 5	±0.10		SCALE: 1:1		PROJ: 	
					DRAWING NO. _____		SHEET 1 OF 1	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			