




linear dimension(Tolerances Standard GB/T 14486-2008)								—   		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60




PCB LAYOUT



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	21.09.28

UL/CUL 技术参数		UL/CUL Technical Data				
等级	Use Group		B	C	D	
额定电压	Rated Voltage	[V]	600	-	-	
额定电流	Rated Current	[A]	30	-	-	
接线范围	Wire Range		18-10			
单/多芯线	Solid/Stranded	[AWG]				
IEC 技术参数						
IEC Technical Data						
额定电压	Rated Voltage	[V]	750			
额定电流	Rated Current	[A]	32			
耐电压	Withstanding Voltage		3000V/1Min			
导线截面积	Conductor cross section		4			
硬质/柔性导线	Solid/ flexible	[mm ²]				
材 料 Material						
绝缘材料	Insulation Material		PA66			
阻燃等级	Imflammability		UL94V-0			
导体材料	Contacting Material		铜合金 Copper alloy			
导体表面镀层	Contactive Coating		镀锡 Tin plated			
一般参数 Other Data						
间距	Pitch	[mm]	11.0			
极数	Poles	[P]	02-24			
剥线长度	Stripping Length	[mm]	-			
螺丝	Screw/扭矩	Torque(Max)	M4/1.2			
工作温度	Operating temperatur	[°C]	-40~+105			
引针尺寸	Pin Dimensions	[mm]	5.2			
PCB板孔径	PCB Hole Diameter	[mm]	2.3			

DES.	LQQ	DATE	21.09.28
CHK.	BY	DATE	21.09.28
APP.	CLF	DATE	21.09.28

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1	第三视角 / THIRD ANGLE PROJECTION	版本 / REV	A
						名称 / TITLE	KF65CM-11.0	



慈溪市科发电子有限公司
CIXI KEFA ELECTRONIC CO., LTD