

RoHS Compliant

尺寸表

PIN	DIM A	DIM B	DIM C
6	2.5	3.6	8.6
8	3.5	4.6	9.6
10	4.5	5.6	10.6
12	5.5	6.6	11.6
14	6.5	7.6	12.6
16	7.5	8.6	13.6
18	8.5	9.6	14.6
20	9.5	10.6	15.6
22	10.5	11.6	16.6
24	11.5	12.6	17.6
26	12.5	13.6	18.6
28	13.5	14.6	19.6
30	14.5	15.6	20.6
32	15.5	16.6	21.6
34	16.5	17.6	22.6
36	17.5	18.6	23.6
38	18.5	19.6	24.6
40	19.5	20.6	25.6
42	20.5	21.6	26.6
44	21.5	22.6	27.6

NOTES:

1.MATERIAL:

HOUSING: HIGH TEMPERATURE THERMOPLASTIC
UL94V_0,COLOR:BLACK.

CONTACT: COPPER ALLOYS.

2.PLATING:

UNDERPLATE: NICKEL 50u"

CONTACT AREA: 80u" TIN OVER NICKEL.

3.MULTIMEDIA CARD COMPATIBLE

深圳市敏连达科技有限公司
Shenzhen Minlianda Technology Co.,Ltd.

品名(ITEM NO) 0.5PH 2.0H 立贴抽拉

料号(PART NO) MLD-FPC-05L-XX-H20

单位(UNIT): MM

未注公差
TOLERANCE UNSPECIFIED

版次(REV): A/0

页次(PAGE):1/1

设计 (DESIGN)


柯南

比例(SCALE) 1:1

模号 (MODEL NO)

审核 (CHECKED)

邱敏



X.X ± 0.38
X.XX ± 0.20
X.XXX ± 0.10
X" ± 5"
X.X" ± 2"

图号 (DWG NO)

MLD-2509031032

核准 (APPROVED)

陈镇