

注: 未经许可禁止传输、复制、编辑该文档, 以及利用其内容进行交流

REV	E.C.N NO.	CONTENT	CHK	DATE

NOTES1:

UL Standard

1.

Use group	B	C	D
Rated Current	10A	/	10A
Rated Voltage	300V	/	300V

2.Wire range: 22~16AWG

IEC Standard

1.

Pollution Degree	3	2	2
Overvoltage Category	III	III	II
Rate Impulse Voltage(KV)	/	4KV	/
Rate Voltage(V)	/	320V	/
Rate Current(A)	/	15A	/

2.wire range: 0.2~1.5mm²

NOTES2:

1.Housing: PA66 (UL94V-0)

2.Cover: PA66 (UL94V-0)

3.Clapboard: PA66 (UL94V-0)

4.Pin header: Copper alloy (Sn Plated)

5.Spring: Stainless Steel

6.Button: POM

NOTES3:

1.Pitch: 7.62mm Poles: 02-24P

2.Stripping length: 10-11mm

3.Operating temperature: -40℃~+105℃

4.RoHS Compliance

How to order

MX142R	-	7.62	-	XXP	-	XXXX	-	X	-	X
产品型号		间距		颜色:		极数				A-Z其他定制
				灰色:GY		橙色:OE		01:常规颜色		
				蓝色:BU		红色:RD		02-99:定制颜色		
				黑色:BK		透明色:TT				
				绿色:GN		黄色:YW				Cu:铜
				白色:WE						Fe:铁

ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	CKK	DATE	23.06.20	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
				NAME	MX142R-7.62-XXP
				DWGNO.	



CIXI MAIXU ELECTRONICS CO.,LTD.

慈溪市迈旭电子有限公司

D

C

B

D

C

B

A

Pitch Range In mm			Nominal Dimension Range In mm					—	∩	□
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150	0.1/10		
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°		