

2		1	
REV	E.C.N NO.	CONTENT	CHK DATE



Use group	B	C	D
Rated Current	15A	15A	10A
Rated Voltage	300V	300V	300V

2.Torque value: M3, 4.43Lb.in

3. Wire range: 22~14AWG

IEC Standard

1.	Pollution Degree	3	2	2
	Overvoltage Category	III	III	III
	Rate Impulse Voltage(KV)	/	/	/
	Rate Voltage(V)	/	250V	/
	Rate Current(A)	/	17.5A	/

2. Torque value: M3, 0.5Nm

3.wire range: 1.5mm²

NOTES2:

1.Housing: PA66(UL94V-0)

2.Solder Pin: Copper alloy(Sn Plated)

3.Screw: Steel(M3,Ni Plated)

NOTES3:

1.Pitch: 7.62mm Poles: 02-24P

2.Operating temperature: $-40^{\circ}\text{C}\sim+105^{\circ}\text{C}$

3. RoHS Compliance

How to order

MX25HM - 7.62 - XXP - XXXX - XX - X - X

产品型号 间距 极数 01:常规颜色 0:Y一字螺丝
灰色:GY 橙色:OE 02-99: 1:S十字螺丝
蓝色:BU 红色:RD 定制颜色 2:PS平头十字螺丝
黑色:BK 透明色:TT
绿色:GN 黄色:YW
透明色:TT 白色:WE

Cu:铜
Fe:铁

A-Z其他定制

Pitch Range In mm			Nominal Dimension Range In mm					—		
TO 6	Over 6 TO 10	Over 10 TO 24	TO 30	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150	0.1/10		
										
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°		

ITEM	NAME OF PART		NO. OF PART	Q"TY	MATERIAL		NOTE	
DWG.	CKK	DATE	22.09.14	UNITS	MM	SHEET/OF	1/1	
CHK.		DATE		SCALE	1 : 1	A4		
APP.		DATE		NAME	MX25HM-7.62-XXP			
 CIXI MAIXU ELECTRONICS CO., LTD. 慈溪市迈旭电子有限公司								
				DWGNO				