

[illegible][illegible][illegible][illegible][illegible][illegible]

6

5

4

3

2

1

注：未经许可禁止传播、复制、编辑该文档，以及利用其内容进行交流

REV

E.C.N NO.

CONTENT

CHK

DATE

NOTES1:

UL Standard

1. Use group	B	C	D
Rated Current	/	/	/
Rated Voltage	/	/	/

IEC Standard

1. Pollution Degree	3	2	2
Overvoltage Category	III	III	II
Rate Impulse Voltage(KV)	/	/	/
Rate Voltage(V)	/	/	/
Rate Current(A)	/	/	/

NOTES2:

1.Housing: PA66 (UL94V-0)

NOTES3:

1.Pitch: 5.08mm Poles: 02~24P

2.Stripping length: /

3.operating temperature: -40℃~+105℃

4.RoHS Compliance

How to order

MX2EDGWC

-

5.08

-

XXP

-

XXXX

-

X

产品型号

间距

颜色:
灰色:GY
蓝色:BU
黑色:BK
绿色:GN
白色:WE

极数:
01:常规颜色
02~99:
定制颜色

A-Z其他定制

Pitch Range In mm			Nominal Dimension Range In mm					- ∩ ◇
	Over 6 TO 10	Over 10 TO 24		Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150	0.1/10
TO 6			TO 30	TO 60	TO 100	TO 150		<
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°

ITEM	NAME OF PART		NO. OF PART	Q'TY	MATERIAL		NOTE	
DWG.	CKK	DATE	23.06.20	UNITS	MM	SHEET/OF	1/1	A
CHK.		DATE		SCALE	1: 1	A4		
APP.		DATE						
CIXI MAIXU ELECTRONICS CO.,LTD. 慈溪市迈旭电子有限公司				NAME	MX2EDGWC-5.08-XXP			
				DWGN0.				

[illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible][illegible]