





REV.	DATE	ECN NO.	MODIFICATION	APPROVER
A	2017.04.15	/	初版发行	JASON
		/		



规格:

Specifications:

- 1, 额定电流: 3A AC/DC (使用AWG#22时)
Current rating: 3A AC/DC (AWG#22)
- 2, 额定电压: 250V AC/DC
Voltage rating: 250V AC/DC
- 3, 使用温度范围: -25℃~+85℃ (含通电时温度上升)
Temperature range: -25℃~+85℃
(including temperature rise in applying electrical current)
- 4, 接触电阻: 初期 / 10 mΩ 以下
环境试验后 / 20 mΩ 以下
Contact resistance: Initial value/10mΩ max
After environmental tests/20 mΩ max
- 5, 绝缘电阻: 初期/1000MΩ 以上
Insulation resistance: 1000 MΩ min
- 6, 耐电压: AC 800V/1分钟
Withstanding voltage: 800VAC/minute
- 7, 适用电线范围: AWG#28~#22
Applicable wire: AWG#28 to #22
- 8, 适合的印刷电路板厚度: 1.6mm
Applicable PC board thickness: 1.6mm
- 9, 主体材料: Thermoplastic, UL94-V0, 天然色 (白色)
Housing material: Thermoplastic, UL94-V0, natural (White)
- 10, 端子材料: 黄铜, 镀锡
Terminal material: brass, plating Tin










PCB LAYOUT




GENERAL TOLERANCE				UNITS mm		NAME(INTENDED USE)		ATOM®深圳市爱特姆科技有限公司 SHENZHEN ATOM TECHNOLOGY CO., LTD.		
SELECT	✓			MAT'L		WAFER 2.0 DIP 90° H6.5		TITLE: Wafer2.0mm XP DIP 90° 带定位柱 无K脚		
TOL ON.	1	2	3			PART NO.(INTENDED USE)				
X.XXX	±0.15	±0.05	±0.15	FINISH		WF200**-06***		DWG NO.: ATOM-A03491		
X.XX	±0.25	±0.13	±0.25			APPD:				
X.X	±0.30	±0.25	±0.50	Q'TY		CHKD:		 SCALE 1:1		
X.	±0.38	±0.38	±1.00			DR: DAVID				
ANGLE	±5°							REV. AO		

ACAD GENERATED DRAWING. DON'T CHANGE BY HAND

REV.	DATE	ECN NO.	MODIFICATION	APPROVER
A	2017.04.15	/	初版发行	JASON
		/		



极数	尺寸				ATOM料号
	A	B	C	D	
2	6.00	4.45	2.00	5.00	WF20002-06401
3	8.00	6.45	4.00	7.00	WF20003-*****
4	10.00	8.45	6.00	9.00	WF20004-10402
5	12.00	10.45	8.00	11.00	WF20005-*****
6	14.00	12.45	10.00	13.00	WF20006-06402
7	16.00	14.45	12.00	15.00	WF20007-06402
8	18.00	16.45	14.00	17.00	WF20008-06402
9	20.00	18.45	16.00	19.00	WF20009-*****
10	22.00	20.45	18.00	21.00	WF20010-*****
11	24.00	22.45	20.00	23.00	WF20011-*****
12	26.00	24.45	22.00	25.00	WF20012-*****
13	28.00	26.45	24.00	27.00	WF20013-*****
14	30.00	28.45	26.00	29.00	WF20014-*****
15	32.00	30.45	28.00	31.00	WF20015-*****
16	34.00	32.45	30.00	33.00	WF20016-*****

GENERAL TOLERANCE				UNITS mm		NAME(INTENDED USE)		ATOM®深圳市爱特姆科技有限公司 SHENZHEN ATOM TECHNOLOGY CO.,LTD.				
SELECT	✓			MAT'L		WAFER 2.0 DIP 90° H6.5						
ON.	TOL.	1	2			3	PART NO.(INTENDED USE)					TITLE:
X.XXX	±0.15	±0.05	±0.15			FINISH		WF200**-06***		Wafer2.0mm XP DIP 90° 带定位柱 无K脚		
X.XX	±0.25	±0.13	±0.25			Q'TY		APPD:		DWG NO.:		
X.X	±0.30	±0.25	±0.50	CHKD:				ATOM-A03491				
X.	±0.38	±0.38	±1.00	DR:				DAVID				
ANGLE	±5°											
										SCALE	SHEET	REV.
								1:1		2/2	A0	