

1		2		3		4		5		6		7		8																											
linear dimension (Tolerances Standard GB/T 14486-2008)								—																																	
A	variable range	to	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	over 100 to																															
	tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60																														
											<table><tr><th colspan="2">材质及电镀 MATERIAL</th></tr><tr><td>焊针 Pin header</td><td>铜合金, 镀锡 Copper alloy, Tin plated</td></tr><tr><td>塑件 Housing</td><td>PA66, UL94V-0</td></tr><tr><th colspan="2">电气性能 ELECTRICAL</th></tr><tr><td>参考标准 Stanard</td><td>UL IEC</td></tr><tr><td>额定电压 Rated voltage</td><td>300V 320V</td></tr><tr><td>额定电流 Rated current</td><td>10A 15A</td></tr><tr><td>接触电阻 Contact resistance</td><td>20mΩ</td></tr><tr><td>绝缘电阻 Insulation resistance</td><td>500MΩ/DC500V</td></tr><tr><td>耐电压 Withstanding voltage</td><td>AC1600V/1Min</td></tr><tr><th colspan="2">机械性能 MECHANICAL</th></tr><tr><td>温度范围 Temp. range</td><td>-40℃ ~ +105℃</td></tr><tr><td>瞬时温度 Max. soldering</td><td>+250℃ for 5 Sec</td></tr></table>					材质及电镀 MATERIAL		焊针 Pin header	铜合金, 镀锡 Copper alloy, Tin plated	塑件 Housing	PA66, UL94V-0	电气性能 ELECTRICAL		参考标准 Stanard	UL IEC	额定电压 Rated voltage	300V 320V	额定电流 Rated current	10A 15A	接触电阻 Contact resistance	20mΩ	绝缘电阻 Insulation resistance	500MΩ/DC500V	耐电压 Withstanding voltage	AC1600V/1Min	机械性能 MECHANICAL		温度范围 Temp. range	-40℃ ~ +105℃	瞬时温度 Max. soldering	+250℃ for 5 Sec
材质及电镀 MATERIAL																																									
焊针 Pin header	铜合金, 镀锡 Copper alloy, Tin plated																																								
塑件 Housing	PA66, UL94V-0																																								
电气性能 ELECTRICAL																																									
参考标准 Stanard	UL IEC																																								
额定电压 Rated voltage	300V 320V																																								
额定电流 Rated current	10A 15A																																								
接触电阻 Contact resistance	20mΩ																																								
绝缘电阻 Insulation resistance	500MΩ/DC500V																																								
耐电压 Withstanding voltage	AC1600V/1Min																																								
机械性能 MECHANICAL																																									
温度范围 Temp. range	-40℃ ~ +105℃																																								
瞬时温度 Max. soldering	+250℃ for 5 Sec																																								
PCB LAYOUT											编码原则 (Product Number Code): WJ2EDGV-5.08-XXP-1Y-00A 产品型号 (Series No.) 间距 (Pitch) 极数 (No. of Poles) 客户需求 (Customer Request) 塑体颜色 (Housing Color) <table><tr><td>1: 单倍间距 (Single Pitch)</td><td>2: 双倍间距 (Double Pitch)</td><td>1: 灰色 (Grey)</td><td>6: 红色 (Red)</td></tr><tr><td></td><td></td><td>2: 蓝色 (Blue)</td><td>7: 透明 (Transparent)</td></tr><tr><td></td><td></td><td>3: 黑色 (Black)</td><td>8: 黄色 (Yellow)</td></tr><tr><td></td><td></td><td>4: 绿色 (Green)</td><td>9: 白色 (White)</td></tr><tr><td></td><td></td><td>5: 橙色 (Orange)</td><td></td></tr></table>					1: 单倍间距 (Single Pitch)	2: 双倍间距 (Double Pitch)	1: 灰色 (Grey)	6: 红色 (Red)			2: 蓝色 (Blue)	7: 透明 (Transparent)			3: 黑色 (Black)	8: 黄色 (Yellow)			4: 绿色 (Green)	9: 白色 (White)			5: 橙色 (Orange)							
1: 单倍间距 (Single Pitch)	2: 双倍间距 (Double Pitch)	1: 灰色 (Grey)	6: 红色 (Red)																																						
		2: 蓝色 (Blue)	7: 透明 (Transparent)																																						
		3: 黑色 (Black)	8: 黄色 (Yellow)																																						
		4: 绿色 (Green)	9: 白色 (White)																																						
		5: 橙色 (Orange)																																							
											<table><tr><th colspan="2">第三视角 (THIRD ANGLE PROJECTION)</th><th colspan="2">插拔式接线端子 PLUG-IN TERMINAL BLOCK</th></tr><tr><td>图纸类型 (TYPE)</td><td>CUSTOMER DRAWING</td><td>型号 (NAME)</td><td>WJ2EDGV-5.08-XXP-1Y-00A</td></tr><tr><td>单位 (UNITS)</td><td>mm</td><td>版本 (VERSION)</td><td>A</td></tr><tr><td>尺寸 (SIZE)</td><td>A4</td><td colspan="2" rowspan="3"> 宁波康奈克斯电气有限公司 NINGBO KANGNEX ELECTRIC., LTD.</td></tr><tr><td>比例 (SCALE)</td><td>1:1</td></tr><tr><td>图页 (SHEET)</td><td>1/1</td></tr></table>					第三视角 (THIRD ANGLE PROJECTION)		插拔式接线端子 PLUG-IN TERMINAL BLOCK		图纸类型 (TYPE)	CUSTOMER DRAWING	型号 (NAME)	WJ2EDGV-5.08-XXP-1Y-00A	单位 (UNITS)	mm	版本 (VERSION)	A	尺寸 (SIZE)	A4	宁波康奈克斯电气有限公司 NINGBO KANGNEX ELECTRIC., LTD.		比例 (SCALE)	1:1	图页 (SHEET)	1/1						
第三视角 (THIRD ANGLE PROJECTION)		插拔式接线端子 PLUG-IN TERMINAL BLOCK																																							
图纸类型 (TYPE)	CUSTOMER DRAWING	型号 (NAME)	WJ2EDGV-5.08-XXP-1Y-00A																																						
单位 (UNITS)	mm	版本 (VERSION)	A																																						
尺寸 (SIZE)	A4	宁波康奈克斯电气有限公司 NINGBO KANGNEX ELECTRIC., LTD.																																							
比例 (SCALE)	1:1																																								
图页 (SHEET)	1/1																																								
1		2		3		4		5		6		7		8																											